



Vigor3912適合頻寬使用需求日益增加的企業網路，採用四核心處理器，備有8個WAN介面，包含2個10G SFP+埠提供光纖連線，2個2.5G乙太網路埠口，以及4個GbE埠口。此外Vigor3912同時備有4個GbE LAN介面以應付企業多種應用與服務，提供高速與穩定的企業網路。

NAT

- Connection Number 300K/500K/1000K
- Port Redirection/Open Ports/Port Triggering
- Port Knocking
- Fast NAT
- Server Load Balance

WAN

- Protocol: DHCP/Static IP/PPPoE
- Load Balance
- WAN Connection Fail-over
- Multiple VLAN
- WAN Budget

LAN

- LAN 1 ~ LAN100
- Port-based & Tag-based VLAN
- Bind IP to MAC Address
- Hotspot Web Portal
- LAN Port Mirror/Packet Capturing
- PPPoE Server

Network Feature

- DHCP Client/Relay/Server
- DHCP Option: 1,3,6,51,53,54,58,59,60,61,66,125
- DHCP Pool Support B-Class
- IGMP v2/v3
- Dynamic DNS
- NTP Client
- RADIUS Server/Client
- LDAP Client Support Anonymous & Simple Credentials
- Wake on LAN
- Smart Action
- High Availability (HA)
- DNS Security
- LAN DNS/DNS Forwarding
- SMS/Mail Alert
- Bonjour
- IPv4/IPv6 Static Route
- Dynamic Routing Protocol
 - RIP v1/v2/ng, OSPFv2, BGP
- Policy-based Routing

VPN

- 500 Concurrent VPN Tunnels (include 200 SSL VPN)
- VPN Trunk with Backup/Load Balance
- Protocol: WireGuard, SSL, OpenVPN, IPsec, GRE over IPsec, PPTP, L2TP, L2TP over IPsec
- Encryption:
 - AES-GCM, AES-CBC, 3DES, DES, MPPE
- Authentication:
 - SHA-512, SHA-256, SHA-1, MD5
- IKE v1/v2 Authentication:
 - Pre-shared Key, X.509, Xauth, EAP
- PPP Authentication:
 - TOTP/mOTP, PAP, CHAP, MS-CHAPv2
- Connection: Remote Dial-In, LAN-to-LAN
- VPN Pass-through: IPsec, PPTP, L2TP
- NAT-traversal (NAT-T)
- VPN Wizard
- VPN from LAN
- VPN Isolation
- VPN Packets Capture
- VPN 2FA for Dial-in User & AD/LDAP Server
- VPN Traffic Graph

IP Protocol

- IPv4 • IPv6

Content Security Management

- Object-based:
 - URL Content Filter
 - Web Content Filter
 - APP Enforcement (IM/P2P Blocking)

Firewall

- User-based Firewall
- Rule-based and Object-based (IP/Country/Service) Firewall
- DoS Defense
- Time Schedule Control
- DNS Filter Enhancement

Management

- Web-based User Interface (HTTP/HTTPS)
- Quick Start Wizard
- CLI (Command Line Interface, Telnet/SSH)
- Configuration Backup/Restore
- Built-in Diagnostic Function
- Firmware Upgrade via WUI (HTTPS/HTTP) /ACS (TR-069)/Utility (TFTP)
- Logging via Syslog
- SNMP Management (MIB-II)
- Session Time Out Management
- Multi-level Management Admin/User
- Time Schedule Control
- User Management
- TR-069

Bandwidth Management

- QoS
 - Guarantee bandwidth for VoIP
 - Class-based bandwidth guarantee by user-defined traffic categories
 - DiffServ Code Point Classifying
 - 4-level priority for each direction (Inbound/Outbound)
- Bandwidth Limitation
- Sessions Limitation
- 802.1p and Layer-3 (TOS/DSCP)

Device Management

- AP Management: 50
- Switch Management : 30
- External Devices : 80

Hardware Interface

- 8 LAN/WAN Configurable Ports (2 x 1G/2.5G/10G SFP+, 2 x 10M/100M/1G/2.5G RJ-45, 4 x 10M/100M/1G RJ-45)
- 4 x 10/100/1000Base-Tx LAN Switch, RJ-45
- 2 x USB Host 3.0
- 1 x Console Port, RJ-45
- 1 x Factory Reset Button