

General

- 4K MAC Address Table
- Support Jumbo Frame 12KB
- Packet Buffer Size : 8Mbit
- Forwarding Rate: 33.5Mpps
- Switching Bandwidth : 45Gbps
- 100M, 1G and 2.5G ports for Multi-speed
- Fanless and quiet
- Plug and Play, Easy Use and Quick Install
- Desktop and Wall Mount
- Auto-MDI/MDIX in all Ports
- Loop Detection

Standard Compliance

- IEEE 802.3u 100Base-T
- IEEE 802.3z 1000Base-X
- IEEE 802.3ab 1000Base-T
- IEEE 802.3bz 2500Base-T
- IEEE 802.3ae 10GBase-X
- IEEE 802.3x full duplex operation and flow control capability
- IEEE 802.3 Nway Auto-negotiation
- IEEE 802.1p QoS
- IEEE 802.3az Energy Efficient Ethernet

Hardware Interface

- 5x 10/100/1000/2500MbE ports, RJ-45
- 1x 1G/2.5G/10G SFP port
(SFP does not support DAC at 1G)

Environmental / Physical

- Temperature
 - Operating: 0 ~ 45°C
 - Storage: -40 ~ 70°C
- Humidity
 - Operating: 10 to 90% RH (Non-condensing)
 - Storage: 5 to 95% RH (Non-condensing)

