



VigorAP 1062C

4x4雙頻WiFi 6吸頂式無線基地台



VigorAP 1062C是一款WIFI 6 雙頻無線基地台，2.4G頻段的最高無限速度可達 1.2Gbps，5GHz頻段最高無限速度更可達 4.8Gbps。此無線基地台搭載數2.5G埠以及MU-MIMO技術，支援最多256台同時連線的無線裝置，可在高密度網路環境下提供快速的無線連網體驗，是提升無線網路效率的理想選擇。VigorAP 1062C支援雲端管理，可透過DrayTek VigorACS對此無線基地台進行遠端管理，或是可作為master AP進行無線基地台集中管理，最多可以管理50台LAN端的無線基地台。



Mesh 網路

自動將所有VigorAP連接，輕鬆簡單擴展無線網路



Band Steering

讓支援5GHz頻段的無線設備優先使用5GHz Wi-Fi，享受更好的連線速度



PoE 電源供應

用網路線直接輸入電源以簡化安裝環境，降低佈線成本



AP 強制漫遊

在無線設備移動時，幫助其連線至訊號更好的基地台，提升漫遊體驗



多組 SSID

可將Wi-Fi用戶分配至不同的VLAN，同時支援多種不同的安全標準



WiFi 排程

透過設定Wi-Fi開啟與關閉的時間來控制無線網路存取權限並節省能源



Airtime 公平性

讓每個用戶有相同的傳輸時間，避免老舊設備或訊號太弱的無線用戶降低整個網路的速度



中央 AP 管理

可透過居易Vigor路由器直接設定、維護、監控VigorAP

Dual-Band

Concurrent 5GHz and 2.4GHz

AX6000

1.2Gbps in 2.4GHz and
4.8Gbps* in 5GHz

256 Users

2.4GHz & 5GHz
shared concurrently

1 x 2.5G LAN

PoE Capable Port

*5G maximum wireless speeds may vary depending on regional limitations.

Interface

LAN Port	1 x 2.5G/1G/100M/10M Ethernet, RJ-45 (PoE-PD Support)
Power	1 x DC Power Input
Button	1 x Factory Reset Button

LAN

DHCP	DHCP Server, DHCP Client, DHCP Relay Agent
Static IP	•
Bind IP to MAC	•
802.1q tag-based VLAN	•

WLAN

WiFi 6	•
OFDMA	•
Max. Clients	256
2.4GHz WLAN	802.11b/g/n/ax
5GHz WLAN	802.11a/n/ac wave 2/ax
Antennas	4x Internal PiFA DB
2.4GHz Max. Link Rate (Mbps)	1200
5GHz Max. Link Rate (Mbps)	4800
Operating Mode	AP, Mesh Root, Mesh Node, Range Extender
Max. Number of SSID	16 (8 per band)
Security Mode	OWE, WEP, WPA, WPA2/WPA WPA2, WPA3/WPA2, WPA3
Authentication	Enterprise, Personal
WMM	•
AirTime Fairness	•
Band Steering	•
Roaming	AP-Assisted Roaming, Pre-Authentication, 802.11r, 802.11v, 802.11k
WPS	PIN Code, WPS Button
WDS	Repeater

Objects

MAC Object	•
MAC Group	•
Schedule	•

APP Notifications

System	WUI/SSH/Telnet Login
Wireless LAN	Mesh Node online/offline

Authentication

RADIUS Authentication	•
-----------------------	---

Certificates

Local Certificates	•
Trusted CA	•
Local Services	•
Backup & Restore	•

Security

MAC Address Filter (Max. entry number)	128
---	-----

Monitoring

DHCP Table	•
ARP Table	*
LLDP Neighbors information	•
Web Syslog	•
Internet Detection	•
Clients List	•

Utility

Ping Tool	•
Trace Tool	•
Web CLI	•

System Maintenance

Syslog	•
SNMP	v1, v2c, v3
Firmware Upgrade	HTTP, TFTP, TR-069
Backup/Restore	•
Role-based Privilege	•
System Reboot	•

Management

Service Control	HTTP, HTTPS, Telnet
TR-069	ACS and CPE Setting
Mesh	Node, Root
Virtual AP Controller (Device up to)	50
VigorConnect Management	•
VigorACS Management	•