



VigorSwitch FX2120

12-SFP+ Port Layer 2+ Managed Switch



DrayTek VigorSwitch FX2120 is a full 10 Gigabit switch with 12x SFP+ ports for uplink/downlink and 1x console port. It is well-suited for ISP and enterprise network with intensive data transmission. Supporting OpenFlow 1.3, it's also a future-proofed switch that can be operating in either traditional switch or SDN switch mode.

Equipped with Layer 3 features, including DHCP Server and VLAN Routing, VigorSwitch FX2120 improves local network sustainability and efficiency regardless of the gateway. Furthermore, with IP Conflict Detection & Prevention, ONVIF Surveillance, ping watchdog, and a lot more, this is the balanced switch that brings advanced features into mid-sized environments.



Interface

LAN Port	12 x 1000Mbps/10GMbps SFP+ Ports
Console Port	1 x RJ-45
Button	1 x Factory Reset

Spanning Tree

STP	•
RSTP	•
MSTP	•

Capacity

Buffer Size	16 Mbit
Switching Capacity	240 Gbps
Forwarding Rate	178.56 Mpps (64 bytes)
MAC Address Table	32k
Jumbo Frame	Up to 12KB
L3 Routing Table	•

Layer 3 Features

Static Route	•
VLAN Route	•
DHCP Server	•

Networking Standards

Ethernet Standards	802.3ae 10Base-T 802.3ab 1000Base-T 802.3x Flow Control 802.3 Auto-Negotiation 802.1q Tag-based VLAN 802.1p Class of Service 802.1d STP 802.1w RSTP 802.1s MSTP 802.3ad LACP 802.1ad QinQ 802.1x Port Access Control 802.1AB LLDP 802.3az EEE
--------------------	--

VLAN

Max.Number of VLAN	512
VLAN Type	802.1q Tag-based MAC-based Protocol-Based Management VLAN Voice VLAN Surveillance VLAN
GVRP	•
Q-in-Q	Basic

QoS

Number of QoS Queues	8
Queue Scheduling	SPQ, WRR
CoS (Class of Service)	CoS, DSCP, CoS-DSCP, IP Precedence
Rate Limiting	•

Security

Authentication Server	RADIUS, TACACS+
802.1X/MAC Authentication	•
IP Source Guard	•
Traffic Control	DoS Defense, Storm Control
Dynamic ARP Inspection (DAI)	•
DHCP Snooping	•
IP Conflict Prevention	•
Loop Protection	•

Multicast

IGMP Snooping	v2, v3 (BISS)
IGMP Querier	•
MLD Snooping	v1, v2
Max. Number of Multicast Group	256
Group Throttling/Filtering	•
MVR (Multicast VLAN Registration)	•

Link Aggregation

Max. Number of Group	8
Max. Number of Member in Each Group	8
Type	Static, LACP
Traffic Load Balancing	•

Management

Local Service	HTTP, HTTPS, Telnet, SSH v2
Config Backup/Restore	•
Dual Image	•
2-Level Administration Privilege	•
Access Control	Access List
OpenVPN Client	•
sFlow	•
SNMP	v1, v2c, v3
RMON Group	1, 2, 3, 9
SNTP (Simple Network Time Protocol)	•
LLDP	•
LLDP-MED	•
Mail Alert	Port Status, Port Speed, System Restart, IP Conflict, Hardware Monitor, Device Check, ONVIF IP Cam Snapshot
VigorRouter Management (SWM)	•
VigorConnect Management	•
VigorACS Management	•

ONVIF Surveillance

Discovery	•
Surveillance Topology	•
Real-Time Video Streaming	•
ONVIF Device Maintenance	Device Info, Network Settings, Reboot, Time Settings, Reset to Factory Default

OpenFlow

Version	1.3
Table Size	1920

*The OpenFlow functionality is project-based and must be activated by DrayTek HQ.
Please contact your Sales for further inquiries.

Physical

Operating Temperature	0 to 50°C
Storage Temperature	-20 to 70°C
Operating Humidity	10 to 90% non-condensing
Storage Humidity	5 to 90% non-condensing