# **Dray** Tek



VigorSwitch Q1100x features 2.5GbE ports for LAN and 10G SFP+ ports for uplink/downlink. When used with WiFi 6 VigorAPs (e.g., VigorAP 905), the VigorSwitch Q1100x delivers full WiFi 6 performance to LAN clients. VigorSwitch Q1100x is a high-performance network switch designed to enhance connectivity and efficiency in business and enterprise environments. Supporting features such as VLAN, Storm Control, Quality of Service and Loop Detection, the VigorSwitch Q1100x is an excellence choice for businesses seeking to maintain a stable, secure, and efficient network infrastructure.



#### Interface

8 x 2.5GbE RJ-45

2 x SFP+ Ports

#### Performance

Buffer Size (Mbit)	8
Switching Capacity (Gbps)	80
Forwarding Rate (64 bytes)(Mpps)	59.52
MAC Address Table	16k
Jumbo Frame (KB)	10

#### Standard Compliance

Ethernet Standards

802.3 10Base-T 802.3u 100Base-T 802.3ab 1000Base-T 802.3bz 2.5GBase-T IEEE802.3ae 10GBase-X 802.3x Flow Control 802.3 Auto-Negotiation 802.3ad LACP 802.1AB LLDP 802.3az EEE

# Spanning Tree

STP	•
PSTP	•

#### **VLAN**

VLAN Type	Port-based VLAN
	802.1q Tag-based VLAN*
	Management VLAN

# Multicast

IGMP Snooping	v1, v2	
MLD Snooping	v1, v2	

## QoS

Number of QoS Queues	4
Queue Scheduling	SPQ, WRR
CoS (Class of Service)	CoS, DSCP, CoS-DSCP, IP Precedence
Rate Limiting	•

#### Security

Traffic Control	Storm Control
Loop Protection	•

## Management

Local Service	HTTP, HTTPS
Config Backup/Restore	•
Dual Image	•
Access Control	Access List
SNMP	vl, v2c
SNTP (Simple Network Time Protocol)	•
LLDP	•

# Physical

Operating Temperature	0 to 45°C
Storage Temperature	-20 to 70°C
Operating Humidity	10 to 90% non-condensing
Storage Humidity	5 to 90% non-condensing

